

Superior Motorsports RWD Mod Figure 8 & Bump N Run Rules

- This is a family oriented event, please refrain yourself from displaying any negative emotions (this includes language and hand gestures). These events are about having fun and spending time with family and friends.
- Driver's door hits are illegal. If the hit is deemed by the official to be careless or intentional, you will be disqualified. If you use the door defense repeatedly you will be disqualified.
- Drivers must stay in cars at all times with eye protection, helmet and seat belt on at all times. Drivers must wear long pants, closed toed shoes and long sleeves while competing in vehicle.
- Driver must be 16 years old or older to compete. Any driver that is under 18 must have a parent/ legal guardian sign a release waiver to compete. Release waivers can be found @ www.superiormotorsportllc.com or release forms will be at registration trailer the day of the event. At select shows that have youth heats ages 10-16, a release form must be signed as well.
- No hot rodding in the pits, keep it at an idle while traveling on and off the track.
- Any open door will be cause for disqualification, you are allowed one fire, second fire will be cause for disqualification. You may return in later rounds.
- Rollovers will be rolled back onto there wheels, if deemed safe, they will be allowed to continue on.
- This is not a team event, team driving will not be tolerated. This is a racing competition where first driver to complete their laps, will be the winner.
- THERE IS NO ALCOHOL OR DRUGS ALLOWED IN THE PITS. This includes pit crews. If you or ANY of your crew is caught with alcohol or drugs you will be disqualified.
- All cars WILL have a post race inspection done before any prize money is awarded. Only officials and drivers that won money from the feature will perform inspection.
- Everyone entering the pits or participating must sign the liability waiver.
- All drivers must be registered and vehicle must be inspected 45 minuets prior to start time.
- **Any questions, CALL FIRST. Don't assume anything. The Officials decision is final.**
- Questions call or text Ethan 810-751-0341 or Dylan 810-310-1119

The Regular RWD Figure 8 Derby Class is designed for the use of V-8 automobiles with a maximum 116 inches wheelbase ONLY. No 4x4's, All Wheel Drives, SUV's, FWD or Convertibles.

SAFETY & SET-UP PREPARATION RWD FIGURE 8 & RWD BUMP N RUN

1. RWD STOCK GAS TANK MUST BE REMOVED. An auxiliary tank must be placed on floor pan from mid line of car interior to left side of vehicle behind the driver's seat and no further rearward than front of rear axle.
2. Auxiliary tank must be of steel or a designated plastic fuel tank. Portable marine outboard tank recommended or racing cell.
3. Auxiliary tank must be securely fastened to floor pan or securely mounted to roll cage.
4. ALL GAS LINE THROUGH INTERIOR OF CAR ARE RECOMMENDED TO BE STEEL OR BRAIDED STEEL. If using rubber hose, hose must be fuel injection hose and all connections must be double clamped.
5. Tank must have a secured cap and all gas lines and fittings must be leak-proof.
6. Auxiliary tank must be completely covered and secured. Auxiliary tank cover must be removed for vehicle inspection.
7. Any leakage of fuel will lead to immediate disqualification of car. Electric fuel pumps must have on/off switch. Must be within driver's reach and labeled.
8. ALL GLASS MUST BE COMPLETELY REMOVED FROM AUTOMOBILE. Includes mirrors, tail and headlights, windshield (mud screen is permitted), all door glass (simply rolling door glass down is not allowed) and any broken glass inside automobile must be removed.

9. All interior must be removed from vehicle (carpet, headliner, back seats). **Airbags must be completely removed.**
10. Chrome moldings, ornaments, door handles, or plastic components must be removed. Any protruding front or rear frame horn must be rounded or flattened.
11. Cars must be clean of all debris prior to coming to this event.
12. Driver's window net, if used, must be WEB STYLE and quick release. Must be able to tear off easily in case of emergency. NO steel, screen or permanent fixture of any kind over driver's door window opening.
13. Safety glasses, goggles or shield must be worn for eye protection.
14. Seat belt (LAP BELT ONLY) or 5 point harness is recommended and full helmet with chin strap are required.
15. **Full roll cage and 4 point cage is mandatory.** Top roll bar height must be above driver's head as seated in car. Door protection bars must remain inside door outer sheet metal. Roll bar and cage are designed for protection of the driver and must be welded to frame. **Mandatory chain, cable or bar must be installed between roof and cowl (middle of windshield) to prevent hood from entering driver's compartment.**
16. Battery must be securely fastened and covered. It must be placed inside of car.
17. Must have working brakes at all times.
18. All excessive holes in firewall and front floor pan must be covered.
19. Fender and 1/4 panel wheel arch can be cut, folded or welded for tire clearance.
20. All other doors must be securely fastened by chain, wire, or welded shut.
21. If outer driver's door skin or reinforcement gets ripped off, torn or fall off, car will be disqualified. Car will also be disqualified if any door comes open during competition.
22. Special numbers will be permitted on a first come basis. It is highly recommend to have a roof sign. Cars may be decorated, but only in good taste.
23. Any tires will be allowed, sidewall protectors allowed. **Absolutely NO V Tread or Skid Steer tires.** Tires maybe cut or grooved. Tubed tires are allowed. Tires must pass official's inspection.
24. A minimum of (1) 1 inch lug nuts must be used on all wheels.
25. **ALL CARS MUST HAVE A FULL WIDTH MUD FLAP ACROSS REAR BUMPER. MUD FLAP CAN NOT BE MORE THAN 3" FROM THE GROUND. THIS IS NOT ONLY TO PROTECT THE SUPERIOR MOTORSPORTS CREW AS WELL AS YOUR LOVED ONES IN THE STANDS!!**
26. NO steering knobs. NO starting fluid inside auto during competition.
27. Hoods must be securely fastened down in a minimum of 4 places. Hoods must have a 12" x 12" hole in hood for extinguisher excess in case of a fire. Hood sheet metal must remain over the top of the fan blade. Electric fans are OK. **ALL CARS MUST HAVE A HOOD TO RUN.**
28. All modified exhaust pipes must exit down or straight up through hood.
29. Radiator must remain in original position or be removed. If transmission oil cooler is modified out of its original position, it must be completely covered and steel or braided steel lines used. Anti-freeze should be flushed and only water added.
25. Trunk lid must be wired, chained or welded solid.
26. You may only interchange any stock automotive front bumper. Bumpers maybe stuffed and plated. Bumpers maybe fabricated from steel. **NO BUMPERS MAY HAVE ANY KIND OF POINT OR SHARP PROTRUDING OBJECTS. POINTS AND PROTRUDING OBJECTS WILL BE CUT OFF OR YOU WILL NOT RACE.**

Official's decisions are final. No exceptions.